



WYMIARY ZAWORÓW (mm)

819 (ANSI KL.150)

829 (ANSI KL.300)

ŚREDNICA ZAWORU	819 (ANSI KL.150)										829 (ANSI KL.300)											
	A	B	C	D	E	F	G	H A/F MAX	J Dia. MAX	X Dia.	ISO MTG	A	B	C	D	E	F	G	H A/F MAX	J Dia. MAX	X Dia.	ISO MTG
50 (51.1)	178	74	87.6 86.9	43.8 41.5	-	156	225	14.0	M20x 1.5p	55.0	F07	216	74	87.6 86.9	43.8 41.5	-	156	225	14.0	M20x 1.5p	55.0	F07
80 (76.5)	203	94	112.4 111.6	51.1 48.4	17.2	201	350	15.1	21.1	55.0	F07	283	94	119.9 119.1	55.7 53.0	21.4	214	557	19.3	27.2	70.0	F10
100 (102.3)	229	117	140.6 139.8	55.9 53.2	21.4	235	557	19.3	27.1	70.0	F10	305	132	147.1 146.3	73.0 70.3	28.6	275	850	26.6	33.2	85.0	F12
150 (151.0)	394	179	182.4 181.6	73.0 70.3	28.6	310	850	26.6	33.1	85.0	F12	403	179	194.6 193.8	77.4 74.7	29.6	327	850	30.4	37.9	100.0	F14
200 (203.3)	457	206	237.4 236.6	77.4 74.7	29.6	-	-	30.4	37.8	100.0	F14	502	231	256.2 255.3	88.4 85.5	36.0	-	-	34.5	42.6	130.0	F16

PEŁNY PRZELOT

Z